

100 IWSUB8 AMPLIFIER

Product Data Sheet

100 IWSUB8 Amplifier is a high-power subwoofer amplifier designed for integration, with rack-mountable design. It is able to power up to two 100 IWSUB8 passive subwoofers connected in parallel.



Key points:

- Peak power 200W, continuous power 150W under 4Ω.
- Amplifier able to drive 2 x 100 IWSUB8 subwoofers connected in parallel.
- High-level electronic protection.

Type	Subwoofer amplifier
Power (continuous)	Max 200W, 150W continuous (4Ω)
Minimum load	4Ω
Voltage range	100-120V-60Hz / 220-230V-50Hz
Power consumption	150W
Stand-by power consumption	0.5W
Bandwith	20-250Hz
Subsonic filter	18dB/oct.
Inputs	LFE, Line in L/R
Outputs	Line out L/R and subwoofer power output on speaker terminal
Cord	Detachable IEC power cord
Protection	Dynamic power control, thermal protection, short circuit, fuse, and over-current protection
Dimensions (HxWxD)	1 ^{3/4} (2 ^{1/16} with stands) x 16 ^{7/8} (19 with brackets) x 10 ^{1/2} " [44.5 x 429 x 257mm]
Net weight	6.8lbs (3.1kg)