
Custom Installation CCM682







See nothing, hear everything

The CCM682 is a high performance ceiling-mount speaker that features a 200mm (8in) aramid fiber cone bass/midrange driver and an aluminium dome tweeter in a neat circular die-cast chassis. Its 30mm coil and 100mm magnet ensure an incredibly efficient and reliable speaker with outstanding sound quality. The aluminium tweeter's housing pivots for adjustable off-axis treble response. The speaker also has a three-position EQ switch for a better off-axis response. The bass/midrange driver's diecast chassis provides extra rigidity which results in a cleaner, faster bass. The blue aramid fiber cone means that the unit is well hidden behind the grille but still produces a remarkably clear and dynamic sound. Incorporating QuickDogs[™] and plug-and-play functionality it is quick and easy to install.

Technical Speci ications

Description	2-way in-ceiling system
Drive Units Frequency Range (-6dB)	1x ø25mm (1in) Nautilus [™] swirl loaded aluminium dome tweeter 1x ø200mm (8in) blue aramid fiber cone bass/ midrange
	35Hz – 50kHz
Recommended Amp Power	25 – 150w
Sensitivity SPL (2.83V, 1m)	
Impedance Nominal (min)	89dB
Frame diameter	8Ω (4.5Ω)
Cut-out diameter	290mm (11.4in)
Depth behind surface	250mm (9.8in)
Protrusion	133mm (5.2in)
Pre-mount Kit	4mm (0.2in)
	C8
Back Box	6C
	00

Bowers & Wilkins

www.bowers-wilkins.com

Nautilus and QuickDogs are trademarks of B&W Group Ltd. Copyright © B&W Group Ltd. E&OE

