

# U2

NEXT GENERATION  
STREAMING TRANSPORT



ALL-NEW  
PROCESSOR

DEDICATED  
USB OUTPUT

LINEAR  
POWER SUPPLY

FIBRE  
NETWORK

DSD512  
PCM768

DSD256  
UPSAMPLING

# LUMIN

# U2

# LUMIN

TRANSPORT-ONLY LUMIN FOR COMBINATION WITH AN EXTERNAL DAC

FIRST LUMIN TRANSPORT TO USE NEW ALL-IN-ONE CHASSIS

LATEST PROCESSOR PROVIDES GREATER RESAMPLING FLEXIBILITY

NEW INTEGRATED TOROIDAL LINEAR POWER SUPPLY


NEW DEDICATED "DIRECT-COUPLED" USB DIGITAL AUDIO OUTPUT PORT

FIBRE NETWORK PROVIDES COMPLETE ISOLATION FROM NETWORK DIGITAL NOISE

DUAL-NETWORK INTERFACE WITH BUILT-IN NETWORK SWITCH

DSD512 AND PCM768 PLAYBACK

MQA DECODING



PHYSICAL: 350mm (W), 350mm (D), 60mm (H), 6kg



#### STREAMING PROTOCOL:

UPnP AV protocol with audio streaming extension (OpenHome). Roon Ready. Spotify Connect. TIDAL Connect. Qobuz. FLAC Lossless Radio. TunesIn Radio. AirPlay-compatible. Gapless Playback. On-Device Playlist. Multi-Room (Songcast)

#### SUPPORTED AUDIO FILE FORMATS:

DSD Lossless: DSF (DSD), DIFF (DSD), DoP (DSD)  
 PCM Lossless: FLAC, Apple Lossless (ALAC), WAV, AIFF  
 Compressed (lossy) Audio: MP3, AAC (in M4A container)  
 MQA

#### SUPPORTED SAMPLE RATES & BIT DEPTHS:

PCM, 44.1–768kHz, 16–32-bit, Stereo  
 DSD512 1-bit, Stereo

#### UPSAMPLING RATES & BIT DEPTHS:

Upsampling and downsampling to every supported format up to DSD256/PCM384

#### SUPPORTED CONTROL DEVICES:

Apple devices. iOS 11.0 or later  
 Android devices. Android 4.0 (Ice Cream Sandwich) or later required

#### APP FEATURES:

Native support for TIDAL, MQA, Qobuz and TunesIn Radio. Tidal MQA icons to identify high-res music. Qobuz high-res icons to identify high-res music. Volume control. High-resolution artwork. Artwork caching. Search. Multiple tag handling. Composer tag support. Album-grouping in playlist. Automatic internet links to artists/album/songs. Saving and restoring of playlists (including Tidal and Qobuz)

#### OPTICAL NETWORK:

Industry-standard SFP  
 1000Base-T Gigabit Ethernet  
 Adapter may be needed for your particular switch/cables  
 Use simultaneously with RJ45 (e.g. connect one to router and one to LUMIN L1 or NAS)

#### OTHER INPUTS:

RJ45 1000Base-T Gigabit Ethernet  
 Shared USB ports can also be used for storage, flash drive, USB hard disk (Single-partition FAT32, exFAT and NTFS only)

See website for latest software and app specification

#### DIGITAL AUDIO OUTPUT:

**USB:**  
 Native DSD512 support  
 PCM 44.1-768kHz, 16-32-bit  
**Optical, Coaxial RCA, Coaxial BNC & AES/EUB SPDIF:**  
 PCM 44.1-192kHz, 16-24-bit  
 DSD (DoP, DSD over PCM) 2.8MHz, 1-bit

#### FINISH:

Raw brushed aluminium  
 Black anodised brushed aluminium

#### POWER SUPPLY:

Internal toroidal linear  
 Low-noise linear regulator

#### OTHER:

Leedh Processing lossless digital volume control  
 Compatible with LUMIN Infrared Control Package  
 Programme of Continuous Development – Firmware-upgradable for further features and enhancements

WWW.LUMINMUSIC.COM