Monitor 40.5 XD2





Monitor 40.5 XD2

Technical Information







Technical Specifications

Description:	Monitor 40.5 XD2 loudspeaker
Technical features	
Drive unit	1 x 300mm Harbeth-made bass unit 1 x 200mm Harbeth-made RADIAL4 mid unit 1 x 25mm ferrofluid-cooled tweeter
Frequency range	35Hz - 20kHz, ±3dB free-space, grille on, smooth off-axis response
Impedance	6-8 ohms, easy to drive
Sensitivity	86dB/2.83V/1m axial
Amplifier suggestion	Works with a wide range of amplifiers - suggested from 35W/channel
Power Handling	650W programme
Connectors	Two 4mm Harbeth-branded binding posts
Space needs	Ideally free-space away from walls
Stands	Optimally to bring ears level with tweeters (tweeter: 660mm up from cabinet base)
Dimensions	
Height	750mm
Width	432mm
Depth	388mm (+12mm for grille and binding posts)
Weight	38kg each (without packing)
Finish	Black Ash Cherry Oak Walnut Bosowood

Rosewood

This information is intended as a guide only and reflects the current specification at the time of print. We reserve the right to make changes to the specification.





M40.5 XD2

www.harbeth.co.uk

Harbeth Audio Ltd., 3-4 Enterprise Park, Lindfield, West Sussex, RH16 2LH, UK