



# No.32



No.32 enjoys the rarefied position of elevating our Reference range to an even higher orbit. No.32 retains the exquisite beauty of our curvilinear reference cabinets, an updated 15" (380mm) true carbon fibre driver that boasts 4" (100mm) of total stroke and our ultra-reliable 1,000 watt amp outfitted with thin film capacitors, higher gain and superior limiting.

The net result is a flagship model that stretched the edge of the art further with superior dynamics, richer tonal color, and a freer, more expressive character that opens up the midranges and highs in an unprecedented manner.

## Specifications

TYPE	Closed box, front-firing driver
ACTIVE DRIVER SIZE & MATERIAL	15 in., 380mm long-throw, carbon fibre cone with inverted carbon fibre dust cap
PASSIVE RADIATOR SIZE & MATERIAL	N/A
LOW FREQUENCY EXTENSION	15Hz at -6 dB
INPUT CONNECTORS	High Level Neutrik Speakon, Low Level stereo RCA and XLR, LFE RCA, LFE XLR
OUTPUT CONNECTORS	High Level Neutrik Speakon, LFE XLR, Line XLR
POWER OUTPUT	1,000 watts (RMS)
AMPLIFIER TYPE	Pure Class D
WIRELESS CAPABILITY	Yes - Rel Airship II [required] sold separately
DUAL PARAMETRIC FILTER	Yes

FULLY ELECTRONIC SET SAFE	Yes
D.C. FAULT	Yes
OUTPUT SHORT	Yes
MAINS INPUT VOLTAGE	220-240 volts, 110-120 volts for certain markets
FUSES	7 Amp semi delay 230 volts operation, 15 Amp semi delay 115 volts operation

## Dimensions

W X H X D	29 1/4 x 21 x 32 1/8 in. (743 x 540 x 816 mm)
NET WEIGHT	187 lbs. (85 kg), shipping weight - 225 lbs. (102kg)
FINISH	Piano Black Lacquer, 12 coats

## Supplied Accessories

MAINS LEAD	Yes
NEUTRIK SPEAKON	Yes (10 Meters Nominal)
INTERCONNECT	
USERS MANUAL	Yes

In the interest of product development, REL Acoustics Limited reserve the right to vary these specifications without notice.