

SHL5plus XD2



Harbeth®

SHL5plus XD2

Technical Information



HANDMADE IN ENGLAND
www.harbeth.co.uk

Harbeth Audio Ltd., 3-4 Enterprise Park, Lindfield, West Sussex, RH16 2LH, UK



Technical Specifications

Description: SHL5plus XD2 loudspeaker

Technical features

Drive unit 1 x 200mm Harbeth-made RADIAL4 mid/bass unit
1 x 25mm ferrofluid-cooled tweeter
1 x 20mm dome SuperTweeter

Frequency range 40Hz - 20kHz, ± 3 dB free-space, grille on, smooth off-axis response

Impedance 6 ohms, easy to drive

Sensitivity 86dB/2.83V/1m axial

Amplifier suggestion Works with a wide range of amplifiers - suggested from 25W/channel

Power Handling 150W programme

Connectors Two 4mm Harbeth-branded binding posts

Space needs Overall response optimised for use away from walls

Stands Optimally to bring ears level with tweeters (tweeter: 475mm up from cabinet base)

Dimensions

Height 635mm

Width 322mm

Depth 300mm (+12mm for grille and binding posts)

Weight 15.8kg each (without packing)

Finish Black Ash
Cherry
Oak
Walnut
Rosewood

This information is intended as a guide only and reflects the current specification at the time of print.
We reserve the right to make changes to the specification.