

SECRET - LCR7





The SECRET LCR7 is a 2-way in-wall speaker equipped with two 170mm midrange/bass drivers with a polypropylene membrane, and a 25mm adjustable silk dome tweeter.

Designed for both stereo and home theater use, the LCR7 is a speaker that excels in both horizontal and vertical positions. You can use them as front, center and surround channels in your stereo and home theater setups. Its ultra-thin and magnetic protection grille can be painted to match the colors of your interior.

The bandwidth of 60 Hz to 20,000 Hz makes it possible to accurately reproduce every detail of your favorite music or movies. Offering an efficiency of 90dB and a maximum power handling of 140W, the LCR7 will adapt to any type of amplifier. The crossover also features a protection against potential power surges coming from the amplifier. For optimum performance, the speaker adapts to the acoustic environment thanks to various sound settings. The low and high frequency

levels can be adjusted in 3 positions (-2dB, 0 and +2dB) and the adjustable tweeter, makes it possible to optimize the listening position.

The terminal has push buttons for easy connection of speaker cables with cross-sections thickness ranging from 1.5 to 5mm2

Thanks to its mounting system and shallow depth of 10 cm, the LCR7 is easy to install and guarantees a perfect fit on any type of wall. A mounting template is provided with the speaker for accurate cutting and positioning.

Take the home theater experience to the next level by creating a high-performance multichannel system with a combination of TRIANGLE flush-mount speakers from the SECRET range: EMT7, IWT7 and Tales 340 subwoofer.

FINISH: Black - White grill

TYPE

Surround speaker

BASS/MEDIUM

6,5 inches - Polypropylene Membrane

TWEETER

1 inch - Silk Dome - Adjustable

SENSIBILITY (dB/W/m)

90 dB

BANDWITH (+/- 3dB)

60 Hz - 20 KF

POWER HANDLING (Watts RMS)

140 V

IMPEDANCE (ohms)

8Ω

CUT OFF FREQUENCY

2,7 KHz

TWEETER/WOOFER SETTINGS

-2 / 0 /+2 dB

NEEDED OPENING

14,48 x 7,48 inches

MINIMUM INSTALLATION DEPTH

3,9 inches

DIMENSIONS (W \times H \times D)

15 8 x 8 9 x 3 5 inches

BRUT WEIGHT

4 4 lbs

EAN CODE

366021600709